

SHV-1615

FEATURES



SHV-1615

- ◆ 16CH, 960H , Standalone DVR
- ◆ H.264 High Profile Compression Format
- ◆ DVD RW & 3 pcs SATA
- ◆ Easy Operation on OSD (Graphics), Support R/C and/or Mouse control
- ◆ Diversity of Recording Type (Schedule/Manual/Alarm/Motion)
- ◆ Powerful USB Connections (USB Flash Memory, USB HDD, USB Mobile DVD-RW)
- ◆ Support 3GPP (Mobile Phone /PDA), PTZ Control
- ◆ Recording Mode & Speed Adjustable:
Continuous Mode / Motion Detection Mode / Event Alarm Mode
- ◆ Snapshot: Time / Date / OSD Display
- ◆ 4 Zones Motion Detection, Separate Sensitivity Adjustable
- ◆ Alarm Input: 6 Ch & Alarm Output: 3 Ch

SPECIFICATIONS

		SHV-1615
System	System Support	Stand Alone DVR
	Operation System	Embedded Linux
	Language	Simplified Chinese, Traditional Chinese, English, etc.
	Video System	PAL / NTSC
Video	System Update	Update Firmware via USB Flash Drive or Through the Network
	Input Channel / Connector	16 ch x BNC
	Input Resolution	960H (PAL:960x576@400fps, NTSC:960x480@480fps) / D1 (PAL:720x576@400fps, NTSC:720x480@480fps)
	Input Compression	H.264
Audio	Output Connector / Channel	VGAx1, CVBSx1, HDMIx1
	Output Resolution	960H (PAL:960x576@400fps, NTSC:960x480@480fps) / D1 (PAL:720x576@400fps, NTSC:720x480@480fps)
	Output Compression	H.264
	Audio	16 ch x RCA, 1 ch x RCA LINE IN,
Alarm	Output Channel / Connector	1 ch x RCA
	Input Channel / Connector	6 ch x Terminal Jack
	Output Channel / Connector	3 ch x Terminal Jack
	Alarm Connection	Used with CMS
Function	Menu	DVR Control or Can Be Set Via Browser
	Split Screen	1, 4, 9, 16
	Image Setting	Brightness, Contrast, Saturation, etc.
	Recording Stream	64K up to 2048 Kbps
Network	Recording Resolution / Speed	PAL:960H@25fps(Adjustable) NTSC:960H@30fps(Adjustable)
	Recording Mode	Manual, Timing, Alarm, Motion Detection
	Video Search	By Time, Event, Channel, Log
	Video Playback	16 ch Playback at the Same Time
Interface	Video Backup	Network Backup, USB Backup (Flash Drives, USB Hard Disk, CDROM)
	Browser	IE 8.0 or Above
	Ethernet	10/100/1000M Auto Negotiation
	Bit Rate Transmission	64Kbps~2Mbps
General	Supported Protocols	HTTP, DHCP, DDNS, PPPoE
	Video Streaming	H.264 Streaming
	Audio Streaming	Two-way Audio
	Users	Support 5 Simultaneous Users
Interface	Security	ID/Password Protection, User Access Log
	Alarm Event	File Upload via Email/Notification via Email, HTTP, DI/DO
	Multicast	NA
	Mobile Client Support	Support iPhone(IOS4 or Above), Android(2.0 or Above), Syband (S60), Black Berry(V5.0, V6.0), Windows Phone (6.0, 6.5)
General	PTZ Interface	RS485
	Ethernet Interface	RJ45 (10/100/1000)
	USB Interface	USB 2.0x3
	Hard Disk Drive	SATA (Support 2TB Hard Disk)
General	Hard Disk Number	DVD-RW & 3 pcs SATA
	Power Supply ; Rated Power	Power Supplier 100~240V 5A ; 250W
	Operation ; Storage Temp.	0°C ~ 45°C ; -10°C ~ 60°C
	Operation ; Storage Humidity	Maximum: RH80% ; RH90%
General	Dimensions	482(W)x450(D)x96(H)mm(2.0U)
	Net Weight	7.63 kg
	Accessories Option	Power Cord x1, Remote Control x1, CD x1,
		Mouse x1, SATA Line x8, HDD Power Cord x2, Screws x1 set