

Digital WD Box Camera (Sony Effio-E)

STC-952EF



FEATURES



Digital WD
610TVL

STC-952EF

- ◆ 1/3" Digital Wide Dynamic Color Camera (Sony Effio-E)
- ◆ Color:610TVL, B/W:630TVL
- ◆ Color:0.05Lux@F1.0, B/W:0.03Lux@F1.0, 0.01Lux@F1.0 (with ICR)
- ◆ Multi-Language OSD Control
- ◆ ATR Digital Powerful 128X WDR (52dB)
- ◆ Anti-Headlight (HLC)
- ◆ 2D Noise Reduction
- ◆ High Contrast Images
- ◆ Ideal for Backlight Environments
- ◆ Mosaic Privacy Mask
- ◆ Advanced Motion Detection Function
- ◆ Picture Quality Adjustable (Contrast/Sharpness/Hue/Gain)



12Vdc±10%
Option: Dual Voltage,
12Vdc/24Vac, 90~260Vac
Tol:±0.5 Unit:mm

SPECIFICATIONS

TV System	PAL	NTSC
Image Sensor	1/3" Sony 760H Super HAD CCD II	
Number of Total Pixels	795(H)x596(V)	811(H)x508(V)
Resolution ; DSP	Color:610TVL, B/W:630TVL ; Sony Effio-E	
Minimum Illumination	Color:0.05Lux@F1.0, B/W:0.03Lux@F1.0, 0.01Lux@F1.0 (with ICR)	
Wide Dynamic Range	ATR Digital WD (ATR:Adaptive Tone-curve Reproduction) ; 128x Normal Camera (52dB)	
Video Output	1.0Vp-p Composite, 75Ω (BNC)	
Signal to Noise Ratio	More than 52dB (AGC off, Weight on)	
Gamma Correction	0.45	
Mechanical IR Cut Filter (ICR)	NA	
IR LED ; Working Distance	NA	
Menu	OSD Control	
Title	TITLE (LOCATION)	
Synchronizing System	INTERNAL	
Digital Day&Night Mode	COLOR / B&W / AUTO	
Electronic Shutter	AUTO (1/50(60)~1/100,000 sec.) / MANUAL: 1/50(60), FL 1/120(100), 1/250, 1/500, 1/1,000, 1/2,000, 1/4,000, 1/10,000 sec.	
Automatic Gain Control	AUTO (4 Steps)	
White Balance	ATW / PUSH / USER1 / USER2 / ANTI CR / MANUAL / PUSH LOCK	
Back Light Compensation	HLC / BLC / OFF	
Flickerless	ON / OFF	
Dynamic Noise Reduction	2D	
Sense Up	NA	
Face Detection	NA	
Language	ENGLISH / JAPANESE / GERMAN / FRENCH / RUSSIAN / PORTUGUESE / SPANISH / SIMPLIFIED CHINESE	
E-Zoom	NA	
Motion Detection ; Privacy	ON / OFF (24x16 Zones) ; ON / OFF (8 Zones Programmable, Mosaic)	
Timer Clock	NA	
Camera Control Interface	NA	
Automatic IRIS ; Connector	VIDEO / DC ; D4 IRIS Jack	
Lens Mount	C / CS mount (With Adaptor)	
Lens, Angle of View (H)	Lens Option: Please See the Page of Lens Series	
Water Resistance	NA	
Max. Breaking Strength	NA	
Power Supply ; Consumption	Standard:12Vdc±10%, Option:12Vdc/24Vac (10.8~39Vdc/24Vac);90~260Vac	
Operation ; Storage Temp.	-10°C~50°C ; -20°C~60°C	
Operation ; Storage Humidity	Maximum: RH80% ; RH90%	
Dimensions	60(W)x50(H)x119(D)mm	
Net Weight	350g	
Accessories Option (Page)	Lens, Bracket	